



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001  
Page 1 of 8

### SECTION 1 CHEMICAL PRODUCT AND IDENTIFICATION

United States Gypsum Company  
550 West Adams Street  
Chicago, Illinois 60661-3637  
A Subsidiary of USG Corporation

Product Safety: 1 (800) 507-8899  
[www.usg.com](http://www.usg.com)  
Version Date: January 1, 2011  
Version: 7

**PRODUCT(S)** SHEETROCK® All Purpose Joint Compound

**CHEMICAL FAMILY /  
GENERAL CATEGORY** Joint Treatment

**SYNONYMS** Joint Compound, Taping Compound, Mud

### SECTION 2 HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW:**  
**ΔWARNING!**

This product is not expected to produce any unusual hazards during normal use. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. Prolonged and repeated breathing of respirable mica dust may cause lung disease (pneumoconiosis).

**POTENTIAL HEALTH EFFECTS** (See Section 11 for more information)

**ACUTE :**

Inhalation	Exposure to dust generated during the handling or sanding of the product may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.
Eyes	Dust can cause temporary mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician.
Skin	None known.
Ingestion	None known.

**CHRONIC:**

Inhalation	Prolonged and repeated breathing of respirable mica dust may cause lung disease (pneumoconiosis). The extent and severity of lung injury correlates with the length of exposure and dust concentration. Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.
Eyes	None known.
Skin	None known.
Ingestion	None known.



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 2 of 8

**TARGET ORGANS:** Eyes, skin and respiratory system.

**PRIMARY ROUTES OF ENTRY:** Inhalation, eyes and skin contact.

**CARCINOGENICITY CLASSIFICATION OF INGREDIENT(S)** All substances listed are associated with the nature of the raw materials used in the manufacture of this product and are not independent components of the product formulation. All substances, if present, are at levels well below regulatory limits. See Section 11: Toxicology Information for detailed information.

MATERIAL	IARC	NTP	ACGIH	CAL- 65
Crystalline silica	1	1	A2	Listed

IARC - International Agency for Research on Cancer: 1- Carcinogenic to humans; 2A – Probably carcinogenic to humans; 2B – Possibly carcinogenic to humans; 3 - Not classifiable as a carcinogen; 4 – Probably not a carcinogen

NTP – National Toxicology Program (Health and Human Services Dept., Public Health Service, NIH/NIEHS): 1- Known to be carcinogen; 2- Anticipated to be carcinogens

ACGIH – American Conference of Governmental Industrial Hygienists: A1 – Confirmed human carcinogen; A2 – Suspected human carcinogen; A3 – Animal carcinogen; A4 - Not classifiable as a carcinogen; A5 – Not suspected as a human carcinogen

CAL-65 – California Proposition 65 “Chemicals known to the State of California to Cause Cancer”

Respirable crystalline silica: IARC: Group 1 carcinogen, NTP: Known human carcinogen. The weight percent of crystalline silica given represents total quartz and not the respirable fraction. The weight percent of respirable silica has not been measured in this product.

Food and Drug Administration [CFR Title 21, v.3, sec 184.1409] – Ground limestone is Generally Recognized as Safe (GRAS).

**POTENTIAL ENVIRONMENTAL EFFECTS:** This product has no known adverse effect on ecology. (See Section 12 for more information.)

### SECTION 3 COMPOSITION, INFORMATION ON INGREDIENTS

MATERIAL	WT%	CAS #
Limestone	>65	1317-65-3
Or Dolomite		16389-88-1
Mica	<20	12001-26-2
Attapulgite	<5	12174-11-7
Vinyl Alcohol Polymer	<5	9002-89-5
Hydroxypropyl Amylopectin Phosphate	<5	113894-92-1
Crystalline Silica	<5	14808-60-7 <sup>^</sup>

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory and the Canadian Domestic Substances List (DSL).

<sup>^</sup>The weight percent for silica represents total quartz and not the respirable fraction.

### SECTION 4 FIRST AID MEASURES

#### FIRST AID PROCEDURES

Inhalation	Remove to fresh air. Leave the area of exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary, however if conditions warrant, contact physician.
------------	--



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 3 of 8

Eyes	In case of contact, do not rub or scratch your eyes. To prevent mechanical irritation, flush thoroughly with water for 15 minutes. If irritation persists, consult physician.
Skin	Wash with mild soap and water. If irritation persists, consult physician.
Ingestion	This product is not intended to be ingested or eaten. If gastric disturbance occurs, call physician.

**MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED:** Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

**NOTES TO PHYSICIAN:** Treatment should be directed at the control of symptoms and the clinical condition.

### SECTION 5 FIRE FIGHTING MEASURES

<b>General Fire Hazards</b>	None known		
<b>Extinguishing Media</b>	Water or use extinguishing media appropriate for surrounding fire.		
<b>Special Fire Fighting Procedures</b>	Wear appropriate personal protective equipment. See section 8.		
<b>Unusual Fire/ Explosion Hazards</b>	None known		
<b>Hazardous Combustion Products</b>	Above 800° C – limestone may decompose to calcium oxide (CaO) and carbon dioxide (CO <sub>2</sub> ).		
<b>Flash Point</b>	Not Determined	<b>Auto Ignition</b>	Not Applicable
<b>Method Used</b>	Not Applicable	<b>Flammability Classification</b>	Not Applicable
<b>Upper Flammable Limit (UFL)</b>	Not Determined	<b>Rate of Burning</b>	Not Applicable
<b>Lower Flammable Limit (LFL)</b>	Not Determined		

### SECTION 6 ACCIDENTAL RELEASE MEASURES

<b>CONTAINMENT:</b> No special precautions. Wear appropriate personal protective equipment. See section 8.
<b>CLEAN-UP:</b> Use normal clean up procedures. No special precautions.
<b>DISPOSAL:</b> Follow all local, state, provincial and federal regulations. Never discharge large releases directly into sewers or surface waters.

### SECTION 7 HANDLING AND STORAGE

<b>HANDLING:</b> Avoid dust contact with eyes and skin. Wear the appropriate eye and skin protection against dust (See Section 8). Minimize dust generation and accumulation. Avoid breathing dust. Wear the appropriate respiratory protection against dust in poorly ventilated areas and if TLV is exceeded (see Sections 2 and 8). Use good safety and industrial hygiene practices.
--



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 4 of 8

**STORAGE:** Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities (see Section 10).

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	WT%	TLV (mg/m <sup>3</sup> )	PEL (mg/m <sup>3</sup> )
Limestone	>65	10	15 (T) / 5 (R)
Or Dolomite		10	15 (T) / 5 (R)
Mica	<20	3 (R)	20 mppcf
Attapulgite	<5	(NE)	(NE)
Vinyl Alcohol Polymer	<5	(NE)	(NE)
Hydroxypropyl Amylopectin Phosphate	<5	(NE)	(NE)
Crystalline Silica	<5	0.025 (R)	0.1 (R)

(T)–Total; (R)–Respirable; (NE)-Not Established; (C)-Ceiling; (STEL)-Short-term exposure limit

(F)-Fume; (Du)-Dust; (M)-Mist

ppm-part per million; f/cc-fiber per cubic centimeter; mppcf- million particles per cubic foot

**ENGINEERING CONTROLS:** Provide ventilation sufficient to control airborne dust levels. If user operations generate airborne dust, use ventilation to keep dust concentrations below permissible exposure limits. Where general ventilation is inadequate, use process enclosures, local exhaust ventilation, or other engineering controls to control dust levels below permissible exposure limits.

**RESPIRATORY PROTECTION:** Wear a NIOSH/MSHA-approved respirator equipped with particulate cartridges when dusty in poorly ventilated areas, and if TLV is exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. If engineering controls are not possible, wear a properly fitted NIOSH/MSHA-approved particulate respirator.

#### OTHER PERSONAL PROTECTIVE EQUIPMENT:

Eye/Face	Wear eye protection, safety glasses or goggles, to avoid possible eye contact.
Skin	Wear gloves and protective clothing to prevent repeated or prolonged skin contact.
General	Selection of Personal Protective Equipment will depend on environmental working conditions and operations.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White to off white	Vapor Density (Air = 1)	Not Applicable
Odor	Low to no odor	Specific Gravity (H <sub>2</sub> O = 1)	~2.3 - 2.6
Odor Threshold	Not Determined	Solubility in water (g/100g)	~ 0.15 g/100 g
Physical State	Solid/ Powder	Partition Coefficient	Not Determined
pH @ 25 ° C	~7.5-9	Auto-ignition Temp	Not Determined
Melting Point	Not Applicable	Decomposition Temp	Not Determined



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 5 of 8

Freezing Point	Not Applicable	Viscosity	Not Applicable
Boiling Point	Not Applicable	Particle Size	Varies
Flash Point	Not Determined	Bulk Density	~ 40-80 lb/ft <sup>3</sup>
Evaporation Rate (BuAc = 1)	Not Applicable	Molecular Weight	Mixture
Upper Flammable Limit (UFL)	Not Determined	VOC Content	Zero g/L
Lower Flammable Limit (LFL)	Not Determined	Percent Volatile	Zero
Vapor Pressure (mm Hg)	Not Applicable		

### SECTION 10 CHEMICAL STABILITY AND REACTIVITY

<b>STABILITY</b>	Stable.
<b>CONDITIONS TO AVOID</b>	Contact with incompatibles (see below).
<b>INCOMPATIBILITY</b>	None known.
<b>HAZARDOUS POLYMERIZATION</b>	None known.
<b>HAZARDOUS DECOMPOSITION</b>	Above 800° C – limestone may decompose to calcium oxide (CaO) and carbon dioxide (CO <sub>2</sub> ).

### SECTION 11 TOXICOLOGICAL INFORMATION

**ACUTE EFFECTS:** None known.

**CHRONIC EFFECTS / CARCINOGENICITY:**

Mica: Prolonged and repeated breathing of respirable mica dust may cause lung disease (pneumoconiosis). The extent and severity of lung injury correlates with the length of exposure and dust concentration.

Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. The weight percent of respirable crystalline silica may not have been measured in this product. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. Smoking in combination with silica exposures increases the risk of cancer. The risk of developing silicosis is dependent upon the exposure intensity and duration.

In June, 1997, IARC classified crystalline silica (quartz and cristobalite) as a human carcinogen. In making the overall evaluation, the IARC Working Group noted that carcinogenicity in humans was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.

IARC states that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).

### SECTION 12 ECOLOGICAL INFORMATION



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001  
Page 6 of 8

**ENVIRONMENTAL TOXICITY:** This product has no known adverse effect on ecology.

<b>Ecotoxicity value</b>	Not determined.
--------------------------	-----------------

### SECTION 13 DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:** Dispose of material in accordance with federal, state, and local regulations. Never discharge directly into sewers or surface waters. Consult with environmental regulatory agencies for guidance on acceptable disposal practices.

### SECTION 14 TRANSPORT INFORMATION

**U.S. DOT INFORMATION:** Not a hazardous material per DOT shipping requirements. Not classified or regulated.

<b>Shipping Name</b>	Same as product name.
----------------------	-----------------------

<b>Hazard Class</b>	Not classified.
---------------------	-----------------

<b>UN/NA #</b>	None. Not classified.
----------------	-----------------------

<b>Packing Group</b>	None.
----------------------	-------

<b>Label (s) Required</b>	Not applicable.
---------------------------	-----------------

<b>GGVSec/MDG-Code</b>	Not classified.
------------------------	-----------------

<b>ICAO/IATA-DGR</b>	Not applicable.
----------------------	-----------------

<b>RID/ADR</b>	None.
----------------	-------

<b>ADNR</b>	None.
-------------	-------

### SECTION 15 REGULATORY INFORMATION

#### UNITED STATES REGULATIONS

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory.

MATERIAL	WT%	3 0 2	3 0 4	3 1 3	CERCLA	CAA Sec. 112	RCRA Code
Limestone Or Dolomite	>65	NL	NL	NL	NL	NL	NL
Mica	<20	NL	NL	NL	NL	NL	NL
Attapulgate	<5	NL	NL	NL	NL	NL	NL
Vinyl Alcohol Polymer	<5	NL	NL	NL	NL	NL	NL



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 7 of 8

Hydroxypropyl Amylopectin Phosphate	<5	NL	NL	NL	NL	NL	NL
Crystalline Silica	<5	NL	NL	NL	NL	NL	NL

Key: NL = Not Listed

SARA Title III Section 302 (EPCRA) Extremely Hazardous Substances: Threshold Planning Quantity (TPQ)

SARA Title III Section 304 (EPCRA) Extremely Hazardous Substances: Reportable Quantity (RQ)

SARA Title III Section 313 (EPCRA) Toxic Chemicals: X= Subject to reporting under section 313

CERCLA Hazardous Substances: Reportable Quantity (RQ)

CAA Section 112 (r) Regulated Chemicals for Accidental Release Prevention: Threshold Quantities(TQ)

RCRA Hazardous Waste: RCRA hazardous waste code

**CANADIAN REGULATIONS**

This product has been classified in accordance with the hazard criteria of Controlled Product regulations and the MSDS contains all the information required by the Controlled Products Regulations. All ingredients of this product are included in the Canadian Domestic Substances List (DSL).

MATERIAL	WT%	IDL Item #	WHMIS Classification
Limestone	>65	Not Listed	D2A
Or Dolomite		Not Listed	Not Listed
Mica	<20	1088	Not Listed
Attapulgate	<5	Not Listed	Not Listed
Vinyl Alcohol Polymer	<5	Not Listed	Not Listed
Hydroxypropyl Amylopectin Phosphate	<5	Not Listed	Not Listed
Crystalline Silica	<5	1406	D2A

IDL Item#: Canadian Hazardous Products Act – Ingredient Disclosure List Item #

WHMIS Classification: Workplace Hazardous Material Information System

**Risk and Safety Phrases defined by European Union Directive 67/548/EEC (Annex III and IV)**

R-Phrase(s): R36/37/38

S-Phrase(s): S51 S38 S39

### SECTION 16 OTHER INFORMATION

**Label Information****Δ WARNING!**

Dust can cause irritation to eyes, skin and respiratory tract. Use wet-sanding to reduce dust created. Wear eye, skin and respiratory protection as necessary per working conditions. If eye contact occurs flush with water for 15 minutes. Do not ingest. If ingested, call physician. Frequent breathing of mica dust can cause lung disease (pneumoconiosis). Product safety information: 800-507-8899 or usg.com. Customer Service: 800 USG-4-YOU (800 874-4968). KEEP OUT OF REACH OF CHILDREN.



# MATERIAL SAFETY DATA SHEET

## SHEETROCK® All Purpose Joint Compound

MSDS #61-320-001

Page 8 of 8

### INFORMATION FOR HANDLING AND IDENTIFICATION OF CHEMICAL HAZARDS

NFPA Ratings:			HMIS Ratings:		<b>HEALTH</b> * <b>1</b>	0 = Minimal Hazard
Health:	1		Health:	1	<b>FLAMMABILITY</b> <b>0</b>	1 = Slight Hazard
Fire:	0		Fire:	0	<b>PHYSICAL HAZARD</b> <b>0</b>	2 = Moderate Hazard
Reactivity:	0		Reactivity:	0	<b>PERSONAL PROTECTION</b> <b>E</b>	3 = Serious Hazard
						4 = Severe Hazard

E – Safety glasses, gloves and dust respirator; \* - Contains silica

#### Key/Legend

ANSI	American National Standards Institute
ACGIH	American Conference of Governmental Industrial Hygienists
CAA	Clean Air Act
CAS	Chemical Abstracts Service (Registry Number)
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act of 1980
CFR	Code of Federal Regulations
DOT	United States Department of Transportation
DSL	Canadian Domestic Substances List
EPA	United States Environmental Protection Agency
EPCRA	Emergency Planning & Community Right-to-know Act
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
MSHA	Mine Safety and Health Administration
NDSL	Canadian Non-Domestic Substances List
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Health and Safety Administration
PEL	Permissible Exposure Limit
PPE	Personal Protection Equipment
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act of 1986
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
UN/NA#	United Nations/North America number
WHMIS	Workplace Hazardous Material Information System

Prepared by:  
 Product Safety  
 USG Corporation  
 550 West Adams Street  
 Chicago, IL 60661-3637

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his/her own particular use.

**END**