

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP BATTERY COAT AERO

Material number : 000000000000010800

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Vehicle Maintenance

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

|            |               |
|------------|---------------|
| Appearance | Liquefied gas |
| Colour     | red           |
| Odour      | solvent-like  |

**GHS Classification**Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 1B  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

H350 May cause cancer.

## Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

P403 Store in a well-ventilated place.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

## Hazardous components

| Chemical name     | CAS-No.   | Concentration [%] |
|-------------------|-----------|-------------------|
| trichloroethylene | 79-01-6   | >= 30 - < 50      |
| propane           | 74-98-6   | >= 10 - < 20      |
| butane            | 106-97-8  | >= 10 - < 20      |
| xylenes           | 1330-20-7 | >= 5 - < 10       |
| 2-butoxyethanol   | 111-76-2  | >= 1 - < 5        |
| ethylbenzene      | 100-41-4  | >= 1 - < 5        |

The exact percentages of disclosed substances are withheld as trade secrets.

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

---

**SECTION 4. FIRST AID MEASURES**

- |   |  |
|---|--|
| General advice  | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.   |
| If inhaled  | : Consult a physician after significant exposure.<br>If unconscious place in recovery position and seek medical advice.  |
| In case of skin contact                                     | : If skin irritation persists, call a physician.<br>Wash off immediately with plenty of water for at least 15 minutes.<br>If on clothes, remove clothes.   |
| In case of eye contact                                      | : Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.<br>If in eyes, rinse with water for 15 minutes.  |
| If swallowed  | : Keep respiratory tract clear.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Take victim immediately to hospital.  |
| Most important symptoms and effects, both acute and delayed | : Effects are immediate and delayed.<br>Symptoms may include irritation, redness, pain, and rash.<br>Chronic effects are delayed and symptoms may not be observed during an exposure.<br>Effects are dependent on exposure (dose, concentration, contact time).<br>Causes serious eye irritation.<br>Suspected of causing cancer.<br>Review section 2 of SDS to see all potential hazards. |
| Notes to physician  | : Treat symptomatically. Symptoms may be delayed.  |

---

**SECTION 5. FIREFIGHTING MEASURES**

- |                                      |   |
|--------------------------------------|---|
| Suitable extinguishing media         | : Alcohol-resistant foam<br>Carbon dioxide (CO2)<br>Dry chemical<br>Water spray jet |
| Unsuitable extinguishing media       | : High volume water jet   |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses.         |
| Hazardous combustion                 | : Carbon dioxide (CO2)  |

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

|   |   |
|---|---|
| products                                      | Carbon monoxide<br>Smoke<br>Chlorine compounds  |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| Further information                           | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.  |

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

|   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions   | : Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Sweep up or vacuum up spillage and collect in suitable container for disposal.  |

---

**SECTION 7. HANDLING AND STORAGE**

|                             |   |
|-----------------------------|---|
| Advice on safe handling     | : Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharges.<br>Provide sufficient air exchange and/or exhaust in work rooms.<br>Always replace cap after use.<br>Dispose of rinse water in accordance with local and national regulations.<br>Do not breathe vapours or spray mist. |
| Conditions for safe storage | : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  |

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

No smoking.  
 Observe label precautions.  
 Keep in a dry, cool and well-ventilated place.  
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents  
 Do not freeze.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

| Components        | CAS-No.   | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis     |
|-------------------|-----------|----------------------------------|---|-----------|
| trichloroethylene | 79-01-6   | TWA                              | 10 ppm  | ACGIH     |
|                   |           | STEL                             | 25 ppm  | ACGIH     |
|                   |           | TWA                              | 100 ppm   | OSHA Z-2  |
|                   |           | CEIL                             | 200 ppm   | OSHA Z-2  |
|                   |           | Peak                             | 300 ppm   | OSHA Z-2  |
|                   |           | TWA                              | 50 ppm<br>270 mg/m3                               | OSHA P0   |
|                   |           | STEL                             | 200 ppm<br>1,080 mg/m3                            | OSHA P0   |
|                   |           | STEL                             | 100 ppm<br>537 mg/m3                              | CAL PEL   |
|                   |           | C                                | 300 ppm   | CAL PEL   |
|                   |           | PEL                              | 25 ppm<br>135 mg/m3                               | CAL PEL   |
| propane           | 74-98-6   | TWA                              | 1,000 ppm   | ACGIH     |
|                   |           | TWA                              | 1,000 ppm<br>1,800 mg/m3                          | NIOSH REL |
|                   |           | TWA                              | 1,000 ppm<br>1,800 mg/m3                          | OSHA Z-1  |
|                   |           | TWA                              | 1,000 ppm<br>1,800 mg/m3                          | OSHA P0   |
|                   |           | PEL                              | 1,000 ppm<br>1,800 mg/m3                          | CAL PEL   |
| butane            | 106-97-8  | TWA                              | 800 ppm<br>1,900 mg/m3                            | NIOSH REL |
|                   |           | TWA                              | 800 ppm<br>1,900 mg/m3                            | OSHA P0   |
|                   |           | PEL                              | 800 ppm<br>1,900 mg/m3                            | CAL PEL   |
| xylenes           | 1330-20-7 | TWA                              | 100 ppm   | ACGIH     |
|                   |           | STEL                             | 150 ppm   | ACGIH     |
|                   |           | STEL                             | 150 ppm<br>655 mg/m3                              | CAL PEL   |
|                   |           | C                                | 300 ppm   | CAL PEL   |
|                   |           | PEL                              | 100 ppm<br>435 mg/m3                              | CAL PEL   |
| 2-butoxyethanol   | 111-76-2  | TWA                              | 20 ppm  | ACGIH     |
|                   |           | TWA                              | 5 ppm   | NIOSH REL |

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

|              |          |      |                      |           |
|--------------|----------|------|----------------------|-----------|
|              |          |      | 24 mg/m3             |           |
|              |          | TWA  | 50 ppm<br>240 mg/m3  | OSHA Z-1  |
|              |          | TWA  | 25 ppm<br>120 mg/m3  | OSHA P0   |
|              |          | PEL  | 20 ppm<br>97 mg/m3   | CAL PEL   |
| ethylbenzene | 100-41-4 | TWA  | 20 ppm               | ACGIH     |
|              |          | STEL | 125 ppm              | ACGIH     |
|              |          | TWA  | 100 ppm<br>435 mg/m3 | NIOSH REL |
|              |          | ST   | 125 ppm<br>545 mg/m3 | NIOSH REL |
|              |          | TWA  | 100 ppm<br>435 mg/m3 | OSHA Z-1  |
|              |          | TWA  | 100 ppm<br>435 mg/m3 | OSHA P0   |
|              |          | STEL | 125 ppm<br>545 mg/m3 | OSHA P0   |
|              |          | PEL  | 5 ppm<br>22 mg/m3    | CAL PEL   |
|              |          | STEL | 30 ppm<br>130 mg/m3  | CAL PEL   |

## Biological occupational exposure limits

| Component       | CAS-No.  | Control parameters                             | Biological specimen | Sampling time  | Permissible concentration | Basis     |
|-----------------|----------|--|---------------------|--|---------------------------|-----------|
| TRICHLOROETHENE | 79-01-6  | Trichloroacetic acid                           | Urine               | End of shift at end of workweek                          | 15 mg/l                   | ACGIH BEI |
| TRICHLOROETHENE |          | Trichloroethanol                               | In blood            | End of shift at end of workweek                          | 0.5 mg/l                  | ACGIH BEI |
| TRICHLOROETHENE |          | Trichloroethylene                              | In end-exhaled air  | End of shift at end of workweek                          |                           | ACGIH BEI |
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic acid (BAA)                        | Urine               | End of shift (As soon as possible after exposure ceases) | 200.mg/g Creatinine       | ACGIH BEI |
| ETHYLBENZENE    | 100-41-4 | Sum of mandelic acid and phenyl glyoxylic acid | Urine               | End of shift (As soon as possible after exposure ceases) | 0.15.g/g creatinine       | ACGIH BEI |
| ETHYLBENZENE    |          | Ethylbenzene                                   | In end-             | Not  |                           | ACGIH BEI |

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

|  |  |   |             |          |  |  |
|--|--|---|-------------|----------|--|--|
|  |  | e | exhaled air | critical |  |  |
|--|--|---|-------------|----------|--|--|

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles  
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Liquefied gas

Colour : red

Odour : solvent-like

Odour Threshold : No data available  
No data available

pH : Not applicable

Melting point/freezing point : Not applicable

Boiling point : 54.4 °C

Flash point :  
not determined

Evaporation rate : 0.75  
n-Butyl Acetate = 1.0

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : 10.5 %(V)

Lower explosion limit : 8 %(V)

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

|  |                          |
|--|--------------------------|
| Vapour pressure                        | : 0.8 hPa                |
| Relative vapour density                | : No data available      |
| Density                                | : 1.25 g/cm <sup>3</sup> |
| Solubility(ies)                        |                          |
| Water solubility                       | : insoluble              |
| Partition coefficient: n-octanol/water | : No data available      |
| Auto-ignition temperature              | : not determined         |
| Thermal decomposition                  | : No data available      |
| Viscosity                              |                          |
| Viscosity, kinematic                   | : No data available      |
| Heat of combustion                     | : 25.75 kJ/g             |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : Stable  |
| Chemical stability                 | : Stable under normal conditions.   |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air.<br>No decomposition if stored and applied as directed. |
| Conditions to avoid                | : Heat, flames and sparks.<br>Extremes of temperature and direct sunlight.                            |
| Incompatible materials             | : Oxidizing agents  |
| Hazardous decomposition products   | : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).<br>Chlorine<br>Phosgene          |

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Potential Health Effects**

|                              |   |
|------------------------------|---|
| Aggravated Medical Condition | : None known.   |
| Symptoms of Overexposure     | : Effects are immediate and delayed.<br>Symptoms may include irritation, redness, pain, and rash.<br>Chronic effects are delayed and symptoms may not be observed during an exposure.<br>Effects are dependent on exposure (dose, concentration, contact time). |



**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

**Carcinogenicity:**

|             |   |          |
|-------------|---|----------|
| <b>IARC</b> | Group 1: Carcinogenic to humans   |          |
|             | trichloroethylene   | 79-01-6  |
| <b>OSHA</b> | Group 2B: Possibly carcinogenic to humans   |          |
|             | ethylbenzene  | 100-41-4 |
| <b>NTP</b>  | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. |          |
|             | Reasonably anticipated to be a human carcinogen   |          |
|             | trichloroethylene   | 79-01-6  |

**Acute toxicity****Product:**

|                           |   |
|---------------------------|---|
| Acute oral toxicity       | : Acute toxicity estimate : > 5,000 mg/kg<br>Method: Calculation method   |
| Acute inhalation toxicity | : Acute toxicity estimate : > 30000 ppm<br>Exposure time: 4 h<br>Test atmosphere: gas<br>Method: Calculation method |
| Acute dermal toxicity     | : Acute toxicity estimate : > 5,000 mg/kg<br>Method: Calculation method   |

**Components:****trichloroethylene:**

|                           |  |
|---------------------------|--|
| Acute oral toxicity       | : LD50 Oral Rat: 4,920 mg/kg                 |
| Acute inhalation toxicity | : LC50 Mouse: 8450 ppm<br>Exposure time: 4 h |
| Acute dermal toxicity     | : LD50 Dermal Rabbit: > 20,000 mg/kg         |

**propane:**

|                           |  |
|---------------------------|--|
| Acute inhalation toxicity | : LC50 Mouse: 1,237 mg/l<br>Exposure time: 2 h |
|                           | LC50 Rat: 658 mg/l<br>Exposure time: 4 h       |
|                           | LC50 Rat: 1,355 mg/l                           |

**butane:**

|                           |  |
|---------------------------|--|
| Acute inhalation toxicity | : LC50 Mouse: 1,237 mg/l<br>Exposure time: 2 h |
|                           | LC50 Rat: 1,355 mg/l                           |

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

---

**Skin corrosion/irritation**

**Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**trichloroethylene:**

**propane:**

**butane:**

**xylenes:**

**2-butoxyethanol:**

**ethylbenzene:**

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information**

**Product:**

Remarks: No data available

Remarks: No data available

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:****trichloroethylene :**

Partition coefficient: n-octanol/water : log Pow: 2.29

**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

**xylenes :**

Partition coefficient: n-octanol/water : Pow: 3.12

**ethylbenzene :**

Partition coefficient: n-octanol/water : Pow: 3.6

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with

**ZEP BATTERY COAT AERO**

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, (LQ), - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

**SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.  
The following substance(s) is/are subject to TSCA 12(b) export  
notification requirements:  
trichloroethylene 79-01-6

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

| Components        | CAS-No. | Component RQ<br>(lbs) | Calculated product RQ<br>(lbs) |
|-------------------|---------|-----------------------|--------------------------------|
| trichloroethylene | 79-01-6 | 100                   | 204                            |

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard  
Fire Hazard

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

Sudden Release of Pressure Hazard  
Chronic Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|                   |          |           |
|-------------------|----------|-----------|
| trichloroethylene | 79-01-6  | 48.9999 % |
| ethylbenzene      | 100-41-4 | 2.63 %    |

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.

|                   |          |
|-------------------|----------|
| trichloroethylene | 79-01-6  |
| ethylbenzene      | 100-41-4 |

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

|                   |         |
|-------------------|---------|
| trichloroethylene | 79-01-6 |
|-------------------|---------|

**The components of this product are reported in the following inventories:**

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

|                        |           |
|------------------------|-----------|
| <b>HEALTH</b>          | <b>3*</b> |
| <b>FLAMMABILITY</b>    | <b>4</b>  |
| <b>PHYSICAL HAZARD</b> | <b>2</b>  |

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

## ZEP BATTERY COAT AERO

Version 3.0

Revision Date 03/17/2017

Print Date 10/27/2017

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

|                |            |
|----------------|------------|
| Version:       | 3.0        |
| Revision Date: | 03/17/2017 |
| Print Date:    | 10/27/2017 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.