

Section 1 - PRODUCT AND COMPANY IDENTIFICATION**Material Name**

SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

Synonyms

Safety-Kleen Premium Gold Solvent; Safety-Kleen Continued Use Product Solvent (CUP); High Flash Degreasing Solvent; Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha; Naphtha, Solvent; Mineral Spirits

Product Use

Cleaning and degreasing metal parts. If this product is used in combination with other products, refer to the Safety Data Sheets for those products.

Restrictions on Use

None known.

MANUFACTURER/SUPPLIERSafety-Kleen Systems, Inc.
2600 North Central Expressway
Suite 200
Richardson, TX 75080
www.safety-kleen.com
Phone: 1-800-669-5740
Emergency Phone #: 1-800-468-1760**IMPORTER/DISTRIBUTOR**Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, Canada L1A 1B2

Phone: 1-800-669-5740
Emergency # 1-800-468-1760**Issue Date**

September 30, 2016

Supersedes Issue Date

June 28, 2016

Original Issue Date

January 26, 1995

Section 2 - HAZARDS IDENTIFICATION**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 4

Aspiration Hazard - Category 1

Specific Target Organ Toxicity - Single Exposure - Category 3 (central nervous system)

GHS Label Elements**Symbol(s)****Signal Word**

Danger

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Hazard Statement(s)

Combustible liquid.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.

Precautionary Statement(s)

Prevention

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection/face protection. Avoid breathing vapor or mist.

Response

In case of fire: Use Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular foam, dry chemical, water spray, or water fog for extinction. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

None known.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-47-8	Petroleum distillates, hydrotreated light	100

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin

IF ON SKIN: Wash with plenty of soap and water. Remove contaminated clothing and wash it before reuse. Get medical attention if irritation develops or persists.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Ingestion

Aspiration hazard. IF SWALLOWED: Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Delayed

May cause damage to central nervous system.

Indication of any immediate medical attention and special treatment needed

IF exposed: Immediately call a POISON CENTER or doctor/physician. Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Media to use includes Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular dry chemical, foam, water spray, and water fog.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Combustible liquid and vapor. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Do not allow run-off from fire-fighting to enter drains or water courses. Closed containers may rupture violently when heated. Empty containers may retain product residue including flammable/explosive vapors. Take precautionary measures against static discharge: May cause fire or explosion.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and other organic compounds.

Advice for firefighters

Wear full protective firefighting gear including self-contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Keep away from ignition sources - No smoking. Keep unnecessary people away, isolate hazard area and deny entry. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Stay away from the ends of tanks. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Do not touch or walk through spilled material. Stop leak if safe to do so. Wear personal protective clothing and equipment. Appropriate engineering controls: Keep unnecessary people away, isolate hazard area and deny entry. Ventilate the area. Avoid breathing vapor or mist. Use foam on spills to minimize vapors. Keep out of water supplies and sewers. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Large spills: Reduce vapors with water spray. Dike for later disposal.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks and flame. Use personal protective equipment as required. When transferring product, trucks and tank cars should be grounded and bonded. Do not breathe vapor or mist. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Keep away from heat and ignition sources. Do not cut, puncture, or weld on or near this container. Empty containers may contain product residue.

Incompatible Materials

Avoid acids, alkalies, oxidizing agents, reducing agents, halogens.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Petroleum distillates, hydrotreated light	64742-47-8
ACGIH:	100 ppm TWA (related to Stoddard solvent)
NIOSH:	350 mg/m ³ TWA (related to Stoddard solvent)
	1800 mg/m ³ Ceiling (15 minutes)
OSHA (US):	500 ppm TWA ; 2900 mg/m ³ TWA (Related to Stoddard solvent)
	100 ppm TWA (Related to Stoddard solvent) ; 525 mg/m ³ TWA (OSHA (Vacated))

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Safety glasses with side shields should be worn at a minimum. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Respiratory Protection

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Glove Recommendations

Wear appropriate chemical resistant gloves. In case of skin contact: neoprene, nitrile, as well as similar materials in protection gloves; do not use natural rubber.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, and/or Lab coat or apron.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid	Physical State	Liquid
Odor	Mild ,hydrocarbon odor	Color	Colorless to pale yellow
Odor Threshold	30 ppm (based on Stoddard Solvent)	pH	Not applicable
Melting Point	-45 F (-43 C)	Boiling Point	350 F (177 C)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	<0.1 (butyl acetate = 1)	Flammability (solid, gas)	Not available
Autoignition Temperature	480 F (249 C)(minimum)	Flash Point	148 F (64 C)
Lower Explosive Limit	0.7 VOL%	Decomposition temperature	Not available
Upper Explosive Limit	5 VOL%	Vapor Pressure	0.2 mm Hg (at 68 F)
Vapor Density (air=1)	5 (air = 1) (approximately)	Specific Gravity (water=1)	0.77 - 0.82 (at 60 F)
Water Solubility	Insoluble	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	6.4 - 6.7 lb/US gal	VOC	100 WT%; 6.4 to 6.7 LB/US gal; 770 to 800 g/l; As per 40 CFR Part 51.100(s); VOC Vapor Pressure: <1.0 mmHg @ 20°C; Product may or may not be considered photochemically reactive (100% by weight); Consult your state or local air district regulations for location specific information.
Molecular Weight	Not available		
Other Information	No additional information is available.		

Section 10 - STABILITY AND REACTIVITY
--

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

Conditions to Avoid

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Avoid acids, alkalies, oxidizing agents, reducing agents, halogens.

Hazardous decomposition products

Not applicable under normal conditions of use and storage. Reference to other sections: Section 5.

Thermal decomposition products

Burning may produce carbon monoxide and other organic compounds.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation, nausea, loss of appetite, headache, drowsiness, dizziness, disorientation, tremors, lung damage, convulsions, coma.

Skin Contact

May cause skin irritation.

Eye Contact

No information on significant adverse effects.

Ingestion

May cause drowsiness or dizziness, headache, loss of coordination, aspiration hazard.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Petroleum distillates, hydrotreated light (64742-47-8)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Inhalation LC50 Rat >5.2 mg/L 4 h

Immediate Effects

May cause central nervous system depression. Aspiration may result in lung damage, respiratory tract irritation. May cause skin irritation.

Delayed Effects

May cause damage to central nervous system.

Irritation/Corrosivity Data

May cause respiratory tract irritation and skin irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

May cause central nervous system depression.

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to central nervous system.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Aspiration hazard

May be fatal if swallowed and enters airways. May cause lung damage.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, kidneys, and eye and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

According to the California Code of Regulations, a toxicity to aquatic life, specifically fish, is determined using an acute 96 hour bioassay. A material is non-hazardous if the LC50 is >500 mg/L. This product passed the bioassay and is considered non-hazardous.

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

This material is believed not to bioaccumulate.

Mobility

Expected to have high mobility in soil.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal. This product, if discarded, is not expected to be a characteristic or listed hazardous waste. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Non-Bulk Packages (less than or equal to 119 gallons): Not regulated. Shipping Name: Cleaning compounds (Petroleum naphtha) (Not US DOT regulated)

Bulk Packages

Shipping Name: COMBUSTIBLE LIQUID, N.O.S., (Petroleum naphtha)

Hazard Class: 3 **UN/NA #:** NA1993 **Packing Group:** III **Required Label(s):** 3

IATA Information:

UN#: Not regulated as a dangerous good

TDG Information:

UN#: Not regulated as a dangerous good

Additional information

Emergency Response Guide Number: 128: Reference: North American Emergency Response Guide Book.

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: yes **Chronic Health:** yes **Fire:** yes **Pressure:** no **Reactivity:** no

U.S. State Regulations

None of this product's components are listed on the state lists from MA, MN, NJ or PA

WARNING! This product can expose you to chemicals including benzene, dichlorobenzene, ethylbenzene, and naphthalene which are known to the State of California to cause cancer and benzene and toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.gov.

Canada Regulations

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

WHMIS Classification

B3; D2B

Component Analysis - Inventory

Petroleum distillates, hydrotreated light (64742-47-8)

US	CA
Yes	DSL

U.S. Inventory (TSCA)

TSCA: All the components of this substance are listed on or are exempt from the inventory.

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision to meet Canadian WHMIS 2015.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA -

Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT (VIRGIN AND RECYCLED)

SDS ID: 82658

National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.