Safety Data Sheet: WIPE-OUT EF, MM

1. PRODUCT AND COMPANY IDENTIFICATION

Supercedes Date 08/20/2014

Product Name WIPE-OUT EF, MM

Recommended use Cleaning agent Information on Manufacturer CHEMSEARCH DIV. OF NCH CORP.

BOX 152170 IRVING, TX 75015

Product Code 0647 Chemical nature Solvent mixture **Emergency Telephone Number** CHEMTREC[®] 800-424-9300 Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Color Straw Pl	nysical State Liquid Odor Vinegar-lik
GHS	
Classification	
Physical Hazards	
Flammable liquids	Category 3
Health Hazard	
Aspiration Toxicity	Category 1
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
pecific target organ systemic toxicity (single exposure)	Category 3
pecific target organ systemic toxicity (repeated exposure)	Category 2
<u>Dther hazards</u> Ione	
lone	
abeling	
<u>Signal Word</u> DANGER	
	∧
<ĸĸĸ×≪≝×⊂∪×a	
	▼
Hazard Statements	Precautionary Statements
H226 - Flammable liquid and vapor	P210 - Keep away from heat, sparks, open flames or hot surfaces.
1315 - Causes skin irritation	P260 - Do not breathe mist or vapor.
H318 - Causes serious eye damage	P271 - Use in a well-ventilated area.
H336 - May cause drowsiness or dizziness	P280 - Wear protective gloves, protective clothing and eye protection.
H305 - May be harmful if swallowed and enters airways	P264 - Wash face, hands and any exposed skin thoroughly after handling.
1373 - May cause damage to organs through prolonged or repeated	P270 - Do not eat, drink or smoke when using this product
exposure	P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position
	comfortable for breathing.
	P312 - Call a physician if unwell.
	P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothin Rinse skin with water or shower
	P332 + P313 - If skin irritation occurs, get medical attention.
	P362 - Take off contaminated clothing and wash before reuse
	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P310 - Immediately call a physician
	P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a
	physician if unwell.
	P403 + P235 - Store in a well-ventilated place. Keep cool
	P233 - Keep container tightly closed
	P501 - Dispose of contents and container in accordance with applicable regulations.
5 % of the mixture consists of ingredient(s) of unknown toxicity	
35 % of the mixture consists of ingredient(s) of unknown toxicity	

Component	CAS-No	Weight %
Alcohols, C9-11, ethoxylated	68439-46-3	15-40
Methyl esters from soy oil	67784-80-9	10-30
Ethyl lactate	97-64-3	10-30
Methyl acetate	79-20-9	10-30
Sodium xylene sulfonate	1300-72-7	3-7

	4. FIRST AID MEASURES
General advice	Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.
Skin Contact	Remove immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES						
Flash Point 85 °F / 29 °C	Method	Seta closed cup				
Flammability Limits in Air % Solvent m Suitable Extinguishing Media	ixture. Upper 16	Lower 3.1				
	nical. Water spray. Use extinguishing measure	s that are appropriate to local circumstances and the				
surrounding environment.						
Specific hazards arising from the che						
	r than air and may spread along floors. Vapors r	may ignite and explode. Material can create slippery				
conditions.						
Protective Equipment and Precaution	-	SH (approved or equivalent) and full protective gear.				
NFPA Health 3	Flammability 3	Instability 0				
HMIS Health 3	Flammability 3	Instability 0				
Personal Precautions Environmental Precautions Methods for Containment Methods for Cleaning Up Neutralizing Agent	Prevent further leakage or spillage if safe to Do not flush into surface water or sanitary Contain spillage, soak up with non-combus diatomaceous earth, vermiculite) and trans regulations (see section 13).	ve all sources of ignition. Ensure adequate ventilation. o do so. Material can create slippery conditions. sewer system. stible absorbent material, (e.g. sand, earth, sfer to a container for disposal according to local / national sorbed material. Pick up and transfer to properly labeled				
	7. HANDLING AND STOR	AGE				
Handling	Keep away from heat and sources of ignitic measures against static discharges. Avoid	on. Avoid breathing vapors or mists. Take precautionary contact with skin, eves and clothing.				
Storage	Keep away from open flames, hot surfaces	and sources of ignition. Store in original container. Keep well-ventilated place. Freezing will affect the physical				
Storage Temperature Storage Conditions	Minimum 35 °F / 2 °C Indoor X Outdoor	Maximum 120 °F / 49 °C Heated Refrigerated				

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	ACGIH TLV	OSHA PEL	NIOSH
Methyl acetate	TWA: 200 ppm	TWA: 200 ppm	3100 ppm
	STEL: 250 ppm	TWA: 610 mg/m ³	STEL 250 ppm
		3	STEL 760 mg/m ³
			TWA: 200 ppm

dequate ventilation, especially in confined areas. Where reasonably practicable this should ved by the use of local exhaust ventilation and good general extraction.
ting safety goggles.
table protective clothing, Impervious gloves.
f inadequate ventilation wear respiratory protection. When workers are facing ations above the exposure limit they must use appropriate certified respirators.
ntective gloves/clothing. Ensure that eyewash stations and safety showers are close to the ion location. Remove and wash contaminated clothing before re-use.
fit sui e o ntra

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Non viscous
Color	Straw	Odor	Vinegar-like
Odor Threshold	Not applicable	Appearance	Transparent
рН	Not applicable	Specific Gravity	0.975
Evaporation Rate	2.0 (Butyl acetate=1)	Percent Volatile (Volume)	71.6
VOC Content (%)	35	VOC Photoreactive (Y/N)	Yes
VOC Content (g/L)	341	Vapor Pressure	34.3 mmHg @ 70°F
Vapor Density	1.9 (Air = 1.0)	Solubility	Emulsifiable
n-Octanol/Water Partition	No data available	Melting Point/Range	No data available
Decomposition Temperature	No data available	Boiling Point/Range	No data available
Flammability (solid, gas)	No data available		
Flash Point	85 °F / 29 °C	Method	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %	Solvent mixture.	Upper 16 Lower 3.1	

10. STABILITY AND REACTIVITY

Chemical Stability Conditions to Avoid Incompatible Products

Hazardous Decomposition Products Possibility of Hazardous Reactions Stable. Hazardous polymerization does not occur. Keep away from open flames, hot surfaces, and sources of ignition Strong oxidizing agents, Strong acids, Strong bases, Amines, Alcohols, Light and/or alkaline metals. Carbon oxides, Sulfur oxides, Aldehydes, Hydrocarbons. None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

The following values are calculated b	pased on chapter 3.1 of the GHS document (Rev. 3, 2009):
Oral LD50	2,733.91
Dermal LD50	3,362.21
Inhalation LC50	
Gas	39,740.39
Mist	39,741.78
Vapor	39,741.78
Principle Route of Exposure	Skin contact, Eye contact, Inhalation.
Primary Routes of Entry	Inhalation, Skin Absorption, Ingestion.
Acute Effects	
Eyes	Severe irritation.
Skin	Causes skin irritation. May be absorbed through the skin in harmful amounts.
Inhalation	Causes respiratory tract irritation. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.
Chronic Toxicity	None known.
Target Organ Effects	Respiratory system, Skin, Central nervous system.
Aggravated Medical Conditions	Respiratory disorders, Skin disorders, Neurological disorders.
Component Information	
A suite Taulation	

Acute Toxicity

Addition of the second se					
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Alcohols, C9-11, ethoxylated	= 1400 mg/kg (Rat)	no data available	no data available	no data available	no data available
Methyl acetate	> 5000 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 ppm (Rat) 4 h	no data available	no data available
Sodium xylene sulfonate	= 1000 mg/kg (Rat)	no data available	no data available	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Methyl acetate	no data available	no data available	no data available	no data available	eyes, CNS, respiratory
					system, skin

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

		12	. ECOLOGICAL INFORMA	TION		
	uct Information ponent Information	No informa	ation available.			
	Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
	Methyl acetate	EC50 > 120 mg/L Desmodesmus subspicatus 72 h	LC50 250 - 350 mg/L Brachydanio rerio 96 h LC50 295 - 348 mg/L Pimephales promelas 96 h	EC50 = 6000 mg/L 16 h EC50 = 6100 mg/L 30 min	EC50 1026.7 mg/L Daphnia magna 48 h	0.18
	stence and Degradability ccumulation ity	No informa	ation available. ation available. ation available.			
		13	. DISPOSAL CONSIDERAT	IONS		
	uct Disposal ainer Disposal		in accordance with local regulati tainers should be taken for local m		aste disposal.	
		14	4. TRANSPORT INFORMAT	ION		
DOT	Proper Shipping Name Hazard Class UN-No Packing Group Description	3 UN1993 III	e Liquids, N.O.S. Iammable Liquids, N.O.S.,(Methyl	acetate),3, PG III		
TDG	Hazard Class UN-No Packing Group	3 UN1993 III				
ICAO						
	UN-No Proper Shipping Name Hazard Class Packing Group Shipping Description	9 III	Eliquids, N.O.S.,(Methyl acetate)	acetate),3, PG III		
ΙΑΤΑ	UN-No Proper Shipping Name Hazard Class Packing Group ERG Code	3 3L	e Liquids, N.O.S.,(Methyl acetate)			
	Shipping Description	UN1993, F	lammable Liquids, N.O.S.,(Methyl	acetate),3, PG III		
IMDG	/IMO Proper Shipping Name Hazard Class UN-No Packing Group EmS No. Shipping Description	3 UN1993 III F-A, S-F	e Liquids, N.O.S.,(Methyl acetate)	acetate),3, PG III (29°C	C.C.)	

15. REGULATORY INFORMATION

TSCA DSL U.S. Federal Regulations SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40 of the Code of Federal Regulations, Part 372.

Complies

Complies

SARA 311/312 Hazardous Categorization

	Pressure Hazard	
Yes Yes Yes	No	No

CERCLA

16. OTHER INFORMATION

Prepared By	Adrienne McKee
Supercedes Date	08/20/2014
Issuing Date	08/27/2014
Reason for Revision	No information available.
Glossary	No information available.
List of References.	No information available.

CHEMSEARCH DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.